

KENWOOD

...pacesetter in Amateur radio

Good
for Satellite
Digital QSOs

Matching Pair

TS-711A/811A VHF/UHF all-mode base stations

Look for
JAS-1
and
PHASE III-C

The TS-711A 2 meter and the TS-811A 70 centimeter all mode transceivers are the perfect rigs for your VHF and UHF operations. Both rigs feature Kenwood's new Digital Code Squelch (DCS) signaling system. Together, they form the perfect "matching pair" for satellite operation.

- **Highly stable dual digital VFOs**

The 10 Hz step, dual digital VFOs offer excellent stability through the use of a TCXO (Temperature Compensated Crystal Oscillator).

- **Large fluorescent multi-function display**

Shows frequency, RIT shift, VFO A/B, SPLIT, ALERT, repeater offset, digital code, and memory channel.

- **40 multi-function memories**

Stores frequency, mode, repeater offset, and CTCSS tone. Memories are backed up with a built-in lithium battery.



- **Versatile scanning functions**

Programmable band and memory scan (with channel lock-out). "Center-stop" tuning on FM. An "alert" function lets you listen for activity on your priority channel while listening on another frequency. **A Kenwood exclusive!**

- **RF power output control**

Continuously adjustable from 2 to 25 watts.

- **Automatic mode selection**

You may select the mode manually using the front panel mode keys. Manual mode selection is verified in International Morse Code.

- **All-mode squelch**

- **High performance noise blanker**

- **Speech processor**

For maximum efficiency on SSB and FM.

- **IF shift**

- **"Quick-Step" tuning**

Vary the tuning characteristics from "conventional VFO feel" to a stepping action.

- **Built-in AC power supply**

Operation on 12 volts DC is also possible.

- **Semi break-in CW, with side tone**

- **VS-1 voice synthesizer (optional)**

More TS-711A/811A information is available from authorized Kenwood dealers.



- **Optional accessories**

- IF-10A computer interface
- IF-232C level translator
- CD-10 call sign display
- SP-430 external speaker
- VS-1 voice synthesizer
- TU-5 CTCSS tone unit
- MB-430 mobile mount
- MC-60A, MC-80, MC-85 deluxe desk top microphones

- MC-48 16-key DTMF, MC-42S UP/DOWN mobile hand microphones
- SW-200A/B SWR/power meters:
 - SW-200A 1.8-150 MHz
 - SW-200B 140-450 MHz
- SWT-1 2-m antenna tuner
- SWT-2 70-cm antenna tuner
- PG-2J DC power cable

Complete service manuals are available for all Trio-Kenwood transceivers and most accessories. Specifications and prices are subject to change without notice or obligation.

KENWOOD

TRIO-KENWOOD COMMUNICATIONS
1111 West Walnut Street
Compton, California 90220